# Design and Landscape Guidelines Design Review Panel Lodgement Checklist REDBANK Belmont



Purchaser's Name:		
Builder:		
Lot No:	Street Name:	
Contact Phone Numb	per:	

	TWO LEVELS OF DESIGN CONTROL	
Design & Landscape Guideline Level	Lot Numbers - Homesites	Rebate
1	Stage 1: 2A - 8A Stage 2: 1, 2, 17, 38 - 50 Belmont East: 862 - 868	\$12,000.00
2	Stage 1: 1A, 9A- 14A Stage 2: 3-16, 18-37, 51-59 Belmont East: 859-861	\$ 8,000.00
Which Level is your Home-s	ite - Level 1, Level 2?	Level

Please be aware of the following:

#### NON COMPLIANCE WITH THE DESIGN GUIDELINES

If you don't comply directly with any of the requirements in the Design and Landscape Guidelines you will have to demonstrate that the intent of the requirement has been achieved in terms of quality of streetscape outcome to justify the non-compliance. Approval of the non-compliance will be at the discretion of the Design Review Panel.

#### **DESIGN EXCELLENCE**

Proposed house designs and architectural features that don't comply with the Design and Landscape Guidelines can be proposed based on 'Design Excellence'. This is when a design is considered to be of high architectural merit but is a different style to what is proposed under the Design and Landscape Guidelines. For example it may be a very modern architectural design but considered of high quality and architectural merit.

If you want to put forward a non-compliant design by justifying Design Excellence you must first put forward a preliminary concept of the design such as a brochure or photo for feedback. Redbank want to avoid purchasers investing money in non-compliant designs that are not considered to achieve Design Excellence so please seek feedback as early as possible prior to formal lodgement with the Design Review Panel.



#### DESIGN AND LANDSCAPE REBATE

If your home and landscaping are completed within 18 months of your land settlement and are in compliance with your approved plans and colour scheme you will be entitled to a Design and Landscape Rebate.

You can apply for your rebate by completing the form in the Design Guidelines document and returning it to the Redbank Sales and Information Centre or by emailing: designreview@redbankcommunities.com.au

Conditions for release of the Design and Landscape Rebate are that:

- No changes (unless endorsed) have occurred to the exterior of the home as reviewed by the Redbank Design Review Coordinator.
- You (and your Builder) have been careful during construction to minimise any damage to the street, footpath, verge, services, public landscape or street tree and that any damage has now been rectified at your cost.
- · Completion of your home, landscaping, driveways and fencing as approved, is within 18 months of settlement of your property.
- Your home and landscape is being maintained to a reasonable standard.

The Design and Landscape Rebate is different for the different levels of design control, see attached schedule of Homesites Levels:

Level 1 Homesites - \$8,000.00

Level 2 Homesites - \$ 5,000.00

Level 3 Homesites - \$ 3,000.00

#### PART 1 - YOUR HOME

#### Architectural Character and Style

Homes at Redbank are intended to be a mix of modern, contemporary and rural character. Front elevation features such as porches, pergolas, verandas and screens are encouraged.

### Architectural Merit (Design Excellence)

Architectural styles such as traditional, contemporary or modern rural style house designs with alternative materials or architectural elements that don't fully comply with these design guidelines can be considered by the Design Review Panel based on Design Excellence and may be approved at their discretion based on architectural merit. If you want to lodge a home that doesn't comply we recommend discussion with a Design Review Panel representative prior to lodgement.

#### Articulation

The front facade and secondary street façade for corner homes must provide articulation including changing wall and roof lines as well as some elements including gables, patios, porches, verandas, single and two storey elements. Articulation is also achieved by including two different wall materials. Materials and colours are to return by at least 2 metres on side elevations.

cted from th	e
	cted from the



	Compliance A	area		Yes	No
Painted, bagged & painted o	r painted rendered masonry (m	aximum 80% of the faca	de)		



Compliance Area	Yes	No
Optional features element of:		
• Stone		
• Lightweight materials such as cladding, fibre cement or seamless, textured and coated materials		
Note: The use of lightweight materials is only permitted to second story or as a design feature element on sing	le storey ho	mes.
Note: The Front facade materials and colours need to wrap around the corners of the walls and return by 2m or	n the side el	evations.
SIDE AND REAR WALLS Walls are to be of:		
Face brickwork or painted, bagged & painted or painted rendered masonry		
Lightweight materials such as cladding fibre cement or seamless, textured and coated materials		
Note: The use of lightweight materials is to be minimised and is only permitted on the second storey as feature supported by a brick veneer below.	s or in areas	s not
Verandas and Porches  Verandas are important architectural elements to promote the architectural character of Redbank.		
<ul> <li>Level 1 Homesites – Must have a covered veranda, balcony or porch a minimum of 1.5 m deep including an entry porch that wraps around the corner of the home site or by a minimum of 50% of the width of the primary frontage and 4m on the frontage of the secondary street for corner lots.</li> </ul>		
• Level 2 Homesites – Must have a covered veranda, balcony or porch a minimum of 1.2m deep that is over 50% the width of the front elevation including an entry porch.		
• Level 3 Homesites – Must have a covered entry porch a minimum of 1.2m deep and 1.2m wide.		
Roof		
The roof is to be of concrete tile, terracotta tile or Colorbond metal roofing.		
Must have a minimum 25% pitch in Level 1 and Level 2 Homesites.		
Roof colours must comply with the Colour Schemes in the Design Guidelines document.		
All homes must have eaves as described below:		
<ul> <li>Level 1 &amp; 2 Homesites – If concrete roof tiles, they must be shingle pattern and a minimum 25-degree pitch and a minimum 450mm eaves.</li> </ul>		
Level 3 Homesites – Must have minimum 20-degree roof pitch and minimum 300mm eaves.		
Windows		
Size and type:		
<ul> <li>Level 1, 2 &amp; 3 Homesites – All windows visible from the street must be double hung or awning type and predominately of vertical proportions.</li> </ul>		
Note: Samples or photos of face bricks and samples of colours of painted rendered external walls are to be submitted with the colours and materials as well as the building and landscape plans for approval.		



Compliance Area	Yes	No
Chimney Elements		
Chimney Elements are encouraged on Level 1 Homesites. A 'chimney element' is an architectural design feature that looks like a chimney but may not be a working chimney. It can be an architectural element, it can be a working chimney or a metal flue concealed by the chimney element. Chimney elements are to be constructed of stone, cladding or masonry and consistent with the house. Chimney elements should not exceed the maximum height of the roofline by 1 metre.		
Garage Doors		
Any garage doors that face the street must be sectional panel or panel lift style doors either simple pattern or plain and not in strong / bright colours. Roller doors are not permitted.		
Satellite Dishes		
Satellite dishes are permitted providing they comply with the following provisions. Dishes must be located, or screened, so they are not visible from the Homesites primary street. Dishes should be located to minimise the visual impact from adjoining homes. Dishes must not be larger than 900mm in diameter.		
Services and Utilities		
Water tanks, air conditioning units, garbage bin storage area, hot water units, clothes drying areas are to be positioned so they can't be seen from the street.		
Granny Flats and Studios		
Only one home can be built on a home site with the exception of granny flats and studios that comply with the NSW Affordable Housing SEPP.		
Colour Schemes		
PAINT AND RENDER COLOURS - should suit your brick and roof materials and be in line with or based on the three Render and Paint Colour Schemes in the Design Guidelines. Each of the colour schemes 'Trees and Grasses', 'Wood and Earth' and 'Shadows and Sunsets' include a number of trim, accent and background colours. Choose one of each for your house. Background and accent colours are to be used for large expanses of the house such as wall materials, cladding or painted masonry. Strong / bright colours are restricted to highlights and trim such as columns and beams, windows and door frames, the front door, gutters and downpipes, handrails and pergolas. Refer to the Colour Schemes on Page 9 of the Design Guidelines document.		
FACE BRICKS - which form the main wall material are to be generally flat-faced, square-edged and not deeply textured. The brick colour is to be generally uniform throughout the brick and provide a consistent wall colour. Pale or white coloured bricks are not permitted. Mid to darker tone bricks are preferred.		
ROOF TILES AND COLORBOND - colours such as mid-range greys to charcoal or in accordance with the Colour Schemes are suitable. Bright red terracotta, bright blue, pure black or pure white are not permitted.		
<b>DRIVEWAYS AND PATHS</b> - in the front yard (private land) must be either a broom finished coloured concrete; plain patterned stenciled or stamped concrete, clay pavers or exposed aggregate. Driveways and paths in the public road reserve (verge areas) must be plain concrete with a broom finish.		



Compliance Area	Yes	No
<b>RETAINING WALLS</b> - in the front or side yard areas that are visible from the street must be masonry and must be either painted masonry to match the house or masonry blocks in charcoal or natural earth colours and tones.		
PART 2 - YOUR HOMESITE		
Sloping Sites — Retaining Walls  Homes are to be designed to respond to the slope of your block. Split level homes and the use of drop edge be encouraged to minimise the use of retaining walls in the private open space areas. The following principles appropriate to the slope of the private open space areas.		
<ul> <li>An elevated entry can be no greater than 1.2m from the existing ground level at that point unless otherwise approved.</li> </ul>		
<ul> <li>Retaining walls on the front boundary should be a maximum height of 500mm unless otherwise approved.</li> </ul>		
Retaining walls within your property should be a maximum height of 1500mm unless otherwise approved.		
To create usable and efficient private open space areas, retaining walls should not be located in your principal private open space. Well-designed terraces will be accepted.		
Retaining walls within your front setback or forward of the home (visible form the street) must be constructed of sandstone or coloured masonry block or painted masonry to match the dwelling.		
Plain concrete block, concrete sleepers and timber retaining walls are not permitted.		
Planting should be used to soften the appearance of retaining walls.		
Driveways		
Driveways must be constructed from the garage to the road kerb prior to occupation of the home.		
• Between the kerb and the boundary of the Homesites the driveway is to be a consistent width between 3m and 4.5m.		
<ul> <li>The driveway must be constructed to its full width using either a broom finished coloured concrete, plain patterned stencilled or stamped concrete, unit pavers or exposed aggregate. No portion of the driveway on the private land (Homesite) is to be uncoloured concrete.</li> </ul>		
The driveway, footpath and cross over in the public street must be plain nature broom finished concrete.		
Driveways are to be sufficiently set back from side boundaries to allow effective screen planting along the boundary.		
The average grade of driveways measured from the boundary of the Homesites to the garage is not to exceed Hawkesbury City Council's requirements.		
Driveways are to be at least 500mm clear of all drainage structures in the kerb and gutter.		
Driveways to corner Homesites must be located at least 6m from the end of the curve in the kerb.		



Compliance Area	Yes	No
Entry Pathway		
The entry path can be connected to the driveway, and the letterbox pier can be located on the boundary next to the driveway.		
Front Fencing		
Fencing along the front boundary or in front of the primary building setback is not permitted.		
Homes should have a masonry letterbox pier to the entry pathway with a planted hedge (minimum 500mm high plants) along the front boundary.		
The masonry pier letterbox should be 900mm high and 350mm x 350mm square constructed of either face brick or painted bagged or rendered brickwork.		
Side and Rear Fencing between Homesites Fencing on common boundaries between Homesites must comply with these provisions:		
Fencing on rear boundaries is limited to 1.8m in height.		
• Fencing on side boundaries is limited to 1.8m in height from 1m behind the front building façade closest to the side boundary.		
Fencing along the side and rear common home site boundaries is to be constructed of lapped and capped timer or masonry materials where a fence height limit of 1.8m is permitted.		
Side gates and block-off fences between the side fence post and house are to be slatted timber and painted a dark colour to match the home.		
Side Gates and Block-Off Fences		
Side gates and block-off fences between the side fence post and house are to be slatted timber and painted a dark colour to match the home		
Corner Homesite Fencing Fencing on boundaries of corner Homesites are to comply with the following provisions:		
<ul> <li>Fencing along the secondary street frontage on the road reserve must be 1.8m in height and should not exceed more than 50% of the length of the home fronting that road boundary measured in accordance with, and is only permitted on one street frontage per corner homesite.</li> </ul>		
Fences on road boundaries must be masonry or painted a colour to match the home with plants planted in front.		
<ul> <li>Must be face brick, bagged or rendered and painted masonry piers with infill panels of painted lapped and capped timber or brushwood, or slatted timber.</li> </ul>		



Compliance Area	Yes	No
Where 1.8m corner home site fencing abutting a road reserve is constructed on top of a retaining wall, the total height of the front fence and retaining wall (measured from ground level on the verge side) is not to exceed 1.8m in height.		
• Fencing is permitted to a height of 1.8m above a retaining wall provided the fence is set back a minimum of 500mm from the front of the retaining wall.		
Fencing on common home site boundaries for corner Homesites is limited to a height of 1.8m.		
Park or Open Space Shared Fence  Homesites that share boundaries with parks and open spaces will be Level 1. Fencing on boundaries of homes with parks or open space must be 1500mm high and built in accordance with the fence detail in the Design Gu		shared
Rural post and 3 rail		
• 1500mm high		
Post 200mm x 100mm		
• Rails 140mm x 35mm		
Treated Pine and/or natural Hardwood		
If treated pine, a dark brown colour appearance paint finish shall apply		
Optional galvanised wire netting. Black mesh preferred if used on dark colour post and rail		
Signs		
Signs for home business must be submitted for approval. All other signs other than real estate signs, builders' signs and development signage are prohibited.		

### PART 3 - YOUR GARDEN